

[54] **PROCESS FOR PRODUCING GLASS
ARTICLE HAVING FRAGMENT RETAINING
AND ALKALI RESISTANT COATING**

[75] Inventor: **Lynn J. Taylor**, Toledo, Ohio

[73] Assignee: **Owens-Illinois, Inc.**, Toledo, Ohio

[21] Appl. No.: **693,616**

[22] Filed: **Jun. 7, 1976**

Related U.S. Application Data

[63] Continuation-in-part of Ser. No. 521,217, Nov. 6, 1974, abandoned.

[51] Int. Cl.² **B32B 17/10; B05D 3/02**

[52] U.S. Cl. **427/55; 215/DIG. 6; 215/12 R; 260/830 TW; 427/386; 427/387; 428/35; 428/415**

[58] Field of Search **427/386, 55, 387; 428/415, 35, 417; 260/830 TW; 215/DIG. 6, 12**
R

[56] **References Cited**

U.S. PATENT DOCUMENTS

3,297,186 1/1967 Wells 428/415
3,299,169 1/1967 Smith 260/830 TW

3,315,035 4/1967 Applegath 428/415
3,391,053 7/1968 Kolb 428/417

FOREIGN PATENT DOCUMENTS

7,104,355 10/1971 Netherlands 428/415

OTHER PUBLICATIONS

Helmreich, "Two Flexible Epoxy Resins", *SPE Journal*, vol. 17, No. 6, Jun., 1961, pp. 583-586.

Primary Examiner—Harry J. Gwinnell

Attorney, Agent, or Firm—Richard D. Heberling

[57] **ABSTRACT**

In accordance with this invention, a chemically convertible liquid coating composition is applied to the surface of a glass substrate and subsequently converted to a solid, protective polymer film by the application of heat or other forms of energy. The chemically convertible coating composition contains at least three ingredients:

- (1) an epoxy resin derived from Bisphenol A and epichlorohydrin;
- (2) a flexibilizing, epoxy resin; and
- (3) a flexibilizing aliphatic amine curing agent.

4 Claims, No Drawings